



# MATTE FINISH PROTECTIVE WAX

## MATT

UNPOLISHED NATURAL STONE AND AGGLOMERATES, QUARRY TILE, RESIN, ENCAUSTIC CEMENT TILE, PVC, LVT, SPC, LAMINATES, RUBBER, TERRACOTTA



### WHAT IT'S FOR

- Ideal for maintaining and giving interior unpolished natural stone, quarry tile and terracotta floors a matte finish.
- Perfect finishing coat over water-based sealers.
- Superficially consolidates surfaces and prevents dusting of brick and natural stone indoor walls and decorative indoor treatments such as stucco, reconstituted stone, or concrete.

### ADVANTAGES

- Gives the surface a natural look.
- Highly concentrated: can be used at various dilutions depending on the desired finish.
- When the treated surface is buffed, it provides a satin finish.
- Completely removable treatment.
- Self-levels.
- Repels dirt and dust.

### HOW TO USE IT

**TO PROTECT WALLS AND FLOORS:** Slightly dilute **MATT** to make it more fluid and easier to apply by adding an 8-ounce glass of water to a liter of product. On a clean and dry surface apply an even coat of **MATT** with a lambswool applicator or brush (for walls). Wait until the surface is completely dry (about one hour) and then apply a second coat perpendicular to the first. The floor may be walked on once the surface is dry (in about one hour). Surfaces treated with **MATT** can be buffed with a wool cloth or floor polishing machine for a shinier finish. On terracotta and highly absorbent stone, we recommend first applying a coat of **MP90 ECO PLUS**. To renew the finish (every 2-3 months): first, clean the surface with **STONECLEAN** for unpolished natural stone and agglomerates, or **CLEANALL** for all other materials. Dilute **CLEANALL** or **STONECLEAN** 1:200 (1-1/2 tablespoons per gallon of water). Then, apply **MATT** diluted 1:10 (1L in 2.5 GAL of water). The floor may be walked on once the surface has dried. To restore the surface finish (once a year): slightly dilute **MATT** by adding an 8-ounce glass of water to a liter of product. Apply the mixture with a lambswool applicator or clean cloth. The floor may be walked on when it is dry.

**Caution:** Wax application is not recommended on outdoor surfaces, in wet environments or any place with standing water (bathrooms, showers). The product may alter the aesthetic appearance of the material. Test the product on a small, inconspicuous area or loose sample before full application. The product may be removed with **PS87**.

**Storage temperature:** Between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 50°F and 86°F (10°C and 30°C).

- ▶ PROVIDES THE SURFACE WITH A DURABLE, LOW SHEEN, NATURAL FINISH.
- ▶ IDEAL FINISH FOR ENCAUSTIC CEMENT TILE.



#### Coverage:

1 Liter (1.06 QT)

#### Terracotta >

323 sq. ft. (30 m<sup>2</sup>),

#### Stone >

323-430 sq. ft. (30-40 m<sup>2</sup>)

Coverage rates are indicative and per coat.



#### Packaging:

1 Liter (1.06 QT) 12 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/04/18 - REV. 02

Fila Chemicals USA, Corp.  
Miami, FL 33172  
tel +1-305-513-0708  
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over  
**200 INTERNATIONAL TOP BRANDS**  
manufacturers of materials for floors and wall coverings

filasolutions.com