

CONSOLE SINK INSTALLATION

BEFORE INSTALLING

This product must be installed by a licensed plumber.

INSTRUCTIONS

Unpack and inspect the product for any shipping damages. If you find damages, do not install.

TOOLS AND MATERIALS:



Pencil



Level



Soft Cloth



Drill



Silicone Sealant



Tape Measure

INSTALLATION

1. Hold the sink, with the legs in place, in the installation location and mark the wall through the mounting holes on the back of the sink.

Important: The sink should be anchored to the wall by two wall mounting hardware. Locate and mark the position of the wall mounts to which you will fasten your sink. We recommend consulting a professional if you are unfamiliar with this type of installation.

2. Drill mounting holes for the anchor or lag bolts using the guides created in the previous step. If the wall is tile, use a masonry drill bit.

3. Secure the sink to the wall with the mounting hardware. After inserting the first fastener, verify that the sink is level. When the sink is properly aligned insert the remaining fasteners.

4. Run a bead of silicone adhesive along the top and bottom of each porcelain leg. Slide the legs in place beneath the sink.

5. Use a level to verify that each leg is perfectly straight.

6. Wipe away any excess silicone with a soft cloth.

7. Let silicone sealant dry for 24 hours before using your console sink. If a lavatory drain is included, move on to the drain Installation section.

